


Test report : CEE-0392/25-1
CEE-0346/25-1
NB : 1722



Type: B
Fuel: Wood Logs

SOLZAIMA

Small Box; N° Série 01-06-00---

Solzaima, SA., Rua da Cova da Areia (E.M. 605), 695, 3750-071 Aguada de Cima
Águeda- Portugal - Made in Portugal

N° DOP DD-099-B

Emissions (13%O₂):

Nom Part

CO : 1250 mg/m³ -
NOx : 200 mg/m³ -
OGC : 100 mg/m³ -
PM : 40 mg/m³ -

Performance:

Nom Part

P : 9,4 kW -
P_W : - -
P_{SH} : 9,4 kW -
η : 80 % -
ρ : 12 Pa -

EN 16510-1:2022 / EN 16510-2-1:2022

Flue gas outlet temperature (Nom-Part):	285 °C- -
Diameter of the flue gas outlet :	150 mm
Fire safety of installation to the chimney :	T 400 G
Seasonal space heating efficiency (η _s) :	72 %
Energy Efficiency Index (EEI) :	106
Energy Efficiency Class :	A
The permissible maximum water operation pressure (P _w - bar):	-
Protective Insulation according to manufacture r's instructions :	-
Power supply voltage (E) :	-
Power supply frequency (f) :	-
Maximum electric power input (W _{max}) :	-
Mass of the appliance (m) :	137 kg
Fuel Type :	Type I
Operation Type :	INT - Intermittent

Minimum distances to combustible materials

Bottom d _B = 0 mm	Floor d _F = 1500 mm	Side radiation area d _L = 1500 mm
Ceiling d _C = 1500 mm	Rear d _R = 400 mm	
Front d _P = 1500 mm	Side d _S = 400 mm	
Non-Comb d _{non} = -		

